

betajoint[®] range

1. Identification of the substance and company

Product name– BetaJoint

RCR Flooring Products Ltd, Mill Close, Lee Mill Industrial Estate, Ivybridge, Devon PL21 9GL

Tel: +44 1752 895288 | Fax:+44 1752 690535

2. Composition / Information on Ingredients

BetaJoint is manufactured from steel.

3. Hazards Identification

When BetaJoint is heated to high temperatures, e.g. during welding or flame cutting, it may emit toxic and irritant fumes, which can cause metal fume fever. Repeated contact with protective coatings on the steel may cause skin complaints or irritate existing skin conditions and as such workers should wear suitable personal protective equipment.

4. First Aid Measures

Skin and eye contact

For lacerations from steel edges. Treat as other lacerations; if required, seek immediate medical attention.

Ingestion

Not relevant.

Inhalation

For the effects of inhaling fumes. Take the person into fresh air and seek immediate medical attention.

5. Fire Fighting Measures

BetaJoint is non-flammable.

6. Accidental release Measures

Not applicable

7. Handling & Storage

Handling

BetaJoint products may be secured by straps which should not be used to lift the product. These straps are under tension and could injure people's eyes or other parts of their body when that tension is released. Certain products may, as a result of processing, be brittle or have residual stress that can cause them to fracture or move significantly. All products are likely to have sharp edges, which could cause lacerations. Sharpening of these products may produce flying particles. Workers should wear suitable protective clothing and equipment such as hand and eye protection. Users of BetaJoint should design their systems of work to account for hazards that might arise e.g tripping hazards onsite.

Storage

When stocking, use suitable racks that will ensure stability.

8. Exposure Controls & Personal Protection

Workers should wear suitable protective clothing and equipment, such as safety spectacles and cut-resistant gloves.

When fumes or dust are generated, users of BetaJoint should ensure adequate ventilation is available. If necessary, local fume extraction should be used. Alternatively, where necessary, those at risk of inhaling fumes should wear suitable respiratory protective equipment to EN 149, FFP3.

betajoint® range

When using processes that are likely to generate dust or fumes, exposures should be kept below current work exposure limits as defined in EH40 or equivalent and also current principles of good practice. To achieve this, adopt good hygiene to remove or suppress contaminants at source (by using local dust or fume extraction as close to the point of creation as possible) or provide suitable ventilation. Where there remains a risk of inhaling dust or fume, workers should wear suitable and adequate respiratory protective equipment such to EN149, FFP3.

9. Physical and Chemical Properties

Composition					Yield Stress (N/mm ²)	Tensile Strength (N/mm ²)	Melting Point °C	Density at 20°C (kg/m ³)
C	Mn	Si	S	P				
0.24 Max	1.5 Max	0.4 Max	0.05 Max	0.05 Max	440 Max	560 Max	450 / 1520	7.85

10. Stability & Reactivity

The product is stable under normal conditions, but when heated to high temperatures, it produces fumes.

11. Toxicological Information

Mechanical working, such as dry grinding or machining, will produce dust of the same composition as the base metal. If the product is heated to high temperatures, e.g during welding or flame cutting, fumes containing oxides of iron and manganese are produced, together with breakdown products of any protective coating that may be on the sheet, all of which may be irritant.

The principal mode of entry into the body is by inhalation. Exposure to airborne iron-oxide fumes, in sufficient concentrations and over long periods of time, may cause benign lung changes. Repeated exposure to manganese can also affect the nervous system, especially the fine control of intentional movement. Prolonged contact with protective coatings in the sheet may cause irritation to the skin and may cause dermatitis.

12. Ecological Information

No known harmful effects

13. Disposal Considerations

	Product BetaJoint	Packaging Pallet and Wooden Supports	Packaging Plastic Wrap and Strapping	Packaging Nails and Staples
Disposal considerations	Recycle or landfill	Incineration or landfill	Incineration or landfill	Recycle or landfill
Hazardous waste	No	No	No	No
Waste code	19 12 02 - ferrous metal	15 01 03 - wooden packaging	15 01 02 - plastic packaging	19 12 02 - ferrous metal
Methods of disposal	Dispose of using licenced waste hauliers and disposal contractors only			

14. Transport Information

The product is not classified as dangerous for carriage

15. Regulatory Information

Plain carbon steel are not classified as 'dangerous for supply' under the Chemical (Hazard Information and Packaging) Regulations.

betajoint[®] range

Material Safety Data Sheet 1.3
19/08/2020

16. Other Information

Some relevant references:

HSE Guidance Notes:

EH26: Occupational skin disease health and safety precautions.

EH40: Occupational exposure limits – current edition

EH42: Monitoring strategies for toxic substances

EH44: Dust in the workplace: general principles of protection (1990)

EH54: Assessment of exposure to fume from welding and allied processes

EH55: The control of exposure to fume from welding, brazing and similar processes